

IMPORTANT

Knape & Vogt insists on the highest standards of quality in the manufacturing of your products. Each piece has been carefully inspected before shipment. In case of a problem, DO NOT RETURN THE ITEM TO THE STORE.

Call Knape & Vogt at:
1-800-253-1561
to help with any problem
or question you may have.

Thank you.



HyLoft's heavy duty shelving systems have patented low-profile brackets so that you can store more items without a large infringing bracket. Each shelf can support up to 150 lbs. All of our products feature a scratch resistant white powder coat finish. Shelves are 15" x 45". There are two shelves per box.



HyLoft's Add-On Storage Hooks add even more versatility to the already popular ceiling storage unit. These hooks hang from any HyLoft Ceiling or Wall mounted unit. They can be used to hang bikes, bags, sports equipment, lawn and garden items, extension cords, and so much more. Each hook is 4" x 6.5", and there are 4 hooks in each package.

HyLoft's Add-On Storage Racks provide endless ways to maximize space and neatly store miscellaneous items. Hang a ladder, lawn tools, lumber, surfboard or any other long items. These hanging racks will attach securely to any HyLoft ceiling or wall storage unit. Each rack is 10" x 32", there are two racks per package.



Accessories




ASSEMBLY INSTRUCTIONS

48" X 48" Ceiling Mounted Shelf

MISSING A PART?

There is no need to return this item to the store. Instead call our TOLL FREE HOTLINE.

1-800-253-1561



Tools Required for 48"x48" Unit:

- Hammer • 7/16" Wrench(11 mm)
- Ratchet and 7/16"(11 mm) Socket
- Stud Finder
- Drill and 3/16"(5 mm) drill bit
- Tape Measure
- Pencil
- Ladder

Parts Included:

- A** 2 wire grids
24"wide(61cm)
- B** 2 support Bars
- C** 4 Angle Brackets
- D** 4 Downrods Bent
- E** 4 Downrods Straight
- F** 8 Lag Screws 5/16" X 2 1/2"
(8mm x 63mm)
- G** 12 Hex Bolts
1/4" X 1/2"(6mm x 13mm)
- H** 20 Hex Nuts
Serrated 1/4"(6mm)
- I** 4 Carriage Bolts 1/4" x 2"
(6mm x 51mm)
- J** 2 Carriage Bolts
8/32 X 1"(4.8 mm x 25.4mm)
- K** 2 Hex Nuts
8/32"(5mm)
- L** 2 Washers
3/16" ID(5mm)
- M** 4 Sinker Nails
- N** 2 Plastic Tie Straps
- O** 4 Hex Bolts 1/4" X 1 1/2"
(6mm x 38mm)
- P** 4 End Plugs
- Q** HyLoft Sticker

Instructional Video



These Instructions
and
Limited Warranty




Before beginning the unit installation, decide where it will work best for you above the open garage door (if room allows) or beyond the open door.

PLEASE NOTE If installing above the open garage door: at least 17" of open space is required between the highest point of door as measured during its upward travel and the ceiling.

Locate the ceiling joists in the area of desired installation and determine the direction in which they are running. In order to adequately disperse the stored load, you should install not more than two HyLoft units on any two ceiling joists. The ceiling Angle Brackets are installed parallel to the ceiling joists. Refer to the diagram below or photos on the package for additional installation clarification.



INSTALL CEILING ANGLES




1B Attach Angles(C) into Ceiling Studs.

Use sinker nail (M) in center hole (with pencil mark) to hold in place and test that it is in the stud.

Pre-drill 3/16" holes for 2 screws.

Use a 7/16" socket wrench or Nut Driver to install two of the 1/4 x 3" screws(F)




2

ATTACH DOWNRODS and SUPPORT BARS

2A Connect two-Piece Downrods(D & E) to center hole in Ceiling Angle



Insert end plugs before attaching



2B Connect Support Bars(B) to Downrods

3

PLACE AND ATTACH GRIDS



You have now completed the installation are ready to load your new HyLoft Storage Unit. **(Maximum 250 lbs. per 48" x 48" unit, evenly distributed)**. Place the sticker provided on a support bar for easy reference information.

Periodically (at least annually) check all connections to ensure that they remain tightly fastened.

Installing Two HyLoft 48 x 48 Units

Follow the instructions above. Multiple HyLoft's may be joined together by using tie straps provided.



MISSING A PART?
There is no need to return
this item to the store.
Instead call our TOLL FREE
HOTLINE.
1-800-253-1561

We appreciate your purchase of the HyLoft storage system. Knap & Vogt has made every effort to supply a quality product that insures a lifetime of trouble-free service. In the event that you have any type of problems and BEFORE RETURNING THE UNIT TO THE SELLER, please call our toll free number 1-800-253-1561

HyLoft 48" x 48" Storage Unit Limited Warranty

Knap & Vogt warrants this product against defects in material or workmanship for the life of the product. Knap & Vogt agrees to either repair the product or replace it at the sole discretion of Knap & Vogt. This warranty does not include any costs associated with the physical installation, removal or return of the HyLoft storage system.

This warranty is valid and enforceable provided that the maximum weight supported by each 48" x 48" HyLoft unit does not exceed 250 pounds, evenly distributed. The customer, dealer, and/or installer releases Knap & Vogt of all claims, which includes the HyLoft unit and the structure it is attached to, if the loaded weight exceeds 250 pounds. The unit must also be installed according to the manufacturer's instructions. At no time should you install more than two HyLoft units on any two ceiling beams (rafters, joists, roof trusses, etc.). All fasteners must be checked and tightened at least annually.

Only the original purchaser of this product is extended this warranty. No warranty work will be provided under this warranty without purchaser's receipt or other proof of the date of original purchase acceptable to Knap & Vogt. Proof of the date of purchase must be provided to Knap & Vogt if the product is returned.

Knap & Vogt limited warranty covers product failure due to defects in materials or workmanship ONLY! It does not cover corrosion, rust or discoloration of its components, or product failure due to misuse, abuse, faulty installation, alteration, lack of reasonable care, or any other failure not related to defects in materials or workmanship.

There are NO other warranties expressed or implied except those stated here in as required by applicable law.

KNAPE & VOGT SHALL NOT BE LIABLE FOR INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THE PRODUCT OR ARISING OUT OF ANY BREACH OF THIS WARRANTY. ALL IMPLIED WARRANTIES, IF ANY, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO THE DURATION OF THIS WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above exclusions or limitations may not apply to you. No other warranty, written or verbal, will be honored for this product. This warranty gives you specific legal rights and you may also have other rights that vary from state to state.

Knap & Vogt is not responsible for damages of merchandise in transit. Repaired or replaced products shall be subject to the terms of this warranty, to be inspected by Knap & Vogt prior to return shipment. Damages incurred during transit should be reported at once to the carrier and a claim should be filed with them.

For assistance with your Knap & Vogt storage system or to obtain warranty service, call Knap & Vogt's Customer Service Department's toll free number at 1-800-253-1561. Please have the product type and date of purchase when you call to avoid delays. *Thank You!*

Knap & Vogt®
Grand Rapids, MI 49505 USA
1-800-253-1561

For more information and frequently asked questions, visit our web site: www.hyloft.com