KV GSlide® GS4260 Push-Open Drawer Slide



Features

- Push-open feature holds a drawer or tray in the closed position until activated by a slight push
- 32mm hole pattern
- Lever disconnect for easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class **Height**: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile: .50" [12.7mm] 1.79" [45.5mm ± 0.3]

Mounting Brackets



Product	Front or Rear	Finish	Pack
GS4340 RB	Rear	Zinc (ZC)	200

Configurations

Bulk (B)	10 Pair and 1 set of instructions per box without screws		
GS4260 Zinc (ZC) Finish			
Size	Bulk (B)		
250mm	GS4260 10		
300mm	GS4260 12		
350mm	GS4260 14		
400mm	GS4260 16		
450mm	GS4260 18		
500mm	GS4260 20		
550mm	GS4260 22		
600mm	GS4260 24		
650mm	GS4260 26		
700mm	GS4260 28		

Recommended Fasteners		KV Part	Finish	Qty
	#7 x 1/2" Phillips Pan Head	8500-93	Zinc (ZC)	1000

Customer Service: 1.800.253.1561 33