
Heavy-Duty

125 lb. Load Class 1/2" Side Clearance Max. Drawer Width: 30"







6505 Over Travel Drawer Slide with Quick Disconnect Rail

The 6505 Over Travel Drawer Slide with Quick Disconnect Rail is designed to accommodate wider and heavier drawers for today's changing trends in the home and workplace.

Applications

- Wood residential, commercial and office furniture
- Architectural, laboratory and school casework
- Store fixtures
- Residential kitchen cabinetry

Specifications

Model: 6505 Over Travel Drawer Slide with Quick Disconnect Rail

Mounting: Side

Disconnect: Quick Disconnect Rail **Hole Pattern**: 32mm and Traditional

Face Frame Mounting: Yes

Type: Ball Bearing Travel: Over Travel Finish: Zinc Plated

Length: 12", 14", 16", 18", 20", 22", 24", 26", 28"

Clearance: .50" + .03"-0" on each side

Height: 2.58" [66mm]: includes quick disconnect rail **Packaging:** Bulk Pack (6505B): all sizes - 5 pair per carton

Action: Telescopic

Slide Configuration: Handed Quick Disconnect Rail: Handed

Rating

Load: 125 lb.

Max. Drawer Width: 30"

As with all Knape & Vogt drawer slides, the 6505 is designed to meet or exceed ANSI performance standards as established by BIFMA, BHMA and KCMA.


Hardware

#8 x 7/16" Wood Screw with #6 truss head

Warranty

Limited Lifetime Warranty

Charted Information



SKU Number	Slide Size inch/mm	Length inch/mm	Travel inch/mm	A inch/mm	B inch/mm	C inch/mm	D inch/mm	E inch/mm	F inch/mm	G Inch/mm	H Inch/mm	J Inch/mm	K Inch/mm	L Inch/mm	M Inch/mm
6505B 12	12" [300mm]	10.57" [268.5mm]	12.80" [325mm]	8.82" [224mm]	-	-	-	-	-	-	0.90" [22.9mm]	7.06" [179.3mm]	-	-	-
6505B 14	14" [350mm]	10.57" [268.5mm]	14.76" [375mm]	8.82" [224mm]	1	ı	ı	-	-	1.06" [26.9mm]	2.90" [73.7mm]	9.18" [233.2mm]	-	-	-
6505B 16	16" [400mm]	14.98" [380.5mm]	16.73" [425mm]	12.60" [320mm]	ı	ı	I	ı	3.06" [77.7mm]	-	1.12" [28.5mm]	9.30" [236.2mm]	4.62" [117.35mm]	-	_
6505B 18	18" [450mm]	14.98" [380.5mm]	18.70" [475mm]	13.86" [352mm]	ı	ı	ı	-	3.06" [77.7mm]	-	1.86" [47.3mm]	10.06" [255.5mm]	4.62" [117.35mm]	-	_
6505B 20	20" [500mm]	14.98" [380.5mm]	20.67" [525mm]	16.38" [416mm]	12.60" [320mm]	-	ı	-	3.06" [77.7mm]	-	1.34" [34.1mm]	11.18" [284mm]	4.62" [117.35mm]	-	_
6505B 22	22" [550mm]	19.39" [492.3mm]	22.64" [575mm]	18.90" [480mm]	17.64" [448mm]	15.12" [384mm]	13.86" [352mm]	11.75" [298.4mm]	3.06" [77.7mm]	-	0.82" [20.9mm]	12.31" [312.7mm]	4.62" [117.35mm]	2.62" [66.55mm]	7.06" [179.3mm]
6505B 24	24" [600mm]	19.39" [492.3mm]	24.61" [625mm]	18.90" [480mm]	15.12" [384mm]	-	ı	-	-	1.06" [26.9mm]	2.83" [71.7mm]	13.06" [331.7mm]	4.62" [117.35mm]	2.62" [66.55mm]	7.06" [179.3mm]
6505B 26	26" [650mm]	23.80" [604.5mm]	26.57" [675mm]	21.42" [544mm]	15.12" [384mm]	_	-	-	3.06" [77.7mm]	1.06" [26.9mm]	2.30" [58.5mm]	14.18" [360.1mm]	4.62" [117.35mm]	2.62" [66.55mm]	7.06" [179.3mm]
6505B 28	28" [700mm]	23.80" [604.5mm]	28.54" [725mm]	23.94" [608mm]	21.42" [544mm]	16.38" [416mm]	_	-	3.06" [77.7mm]	1.06" [26.9mm]	1.79" [45.3mm]	15.31" [388.9mm]	4.62" [117.35mm]	2.62" [66.55mm]	7.06" [179.3mm]