

660 Series Heavy-Duty Round Closet Rod



Applications For closet or other storage applications requiring round closet rods

Load Rating Varies per size* **Mounting** Wall or cabinetry

Features

MaterialCommercial grade steel core with finished wrapFinishesStainless Steel (SS): Attractive, long-lasting,

corrosion resistant finishes


Wall thickness: 0.087"Made in the USA

Available from open stock

* Contact KV Customer service for more information

Dimensions

Standard Pack (6/carton)		
Length		Stainless Steel (SS)
48"	4'	660 SS 48
60"	5'	660 SS 60
72"	6'	660 SS 72
96"	8'	660 SS 96
120"	10'	660 SS 120
144"	12'	660 SS 144



Accessories



632 Line Bore Flange

1 screw hole for extra mounting strength. Two 5mm pins for pre-drilled applications.

Standard Pack (10/carton)	
Chrome	632 CHR



730 End Cap

Use with KV 660 or 750 1 closet rods (inside diameter: 29/32").

Standard Pack (50/box)	
Anochrome	730 ANO



734 Wall-Mount Flanges

2 screw holes on vertical 2" centers.

Standard Pack (50/box w/screws)	
Brass	734 BR
Chrome	734 CHR



742 Three-Tier Wall-Mount Flange

3 screw holes. For custom applications.

Standard Pack (12/box w/screws)	
Chrome	742 CHR



735 Wall-Mount Flanges

2 screw holes on horizontal 2" centers.

Standard Pack (50/box w/screws)		
Brass	735 BR	
Chrome	735 CHR	



757 Pilaster Flange

Mounts to KV 233 or 255 pilaster standards.

Standard Pack (100/box)	
Anochrome	757 ANO



760 Center Support

Provides 24" of center support.

Standard Pack (12/box (w/screws))	
Anochrome	760 ANO

660 Series Heavy Duty Round Closet Rod



1. Product Name

660 Series Heavy-Duty Round Closet Rod.
For closet or other storage applications requiring round closet rods.

2. Manufacturer

Knape & Vogt* Manufacturing Company 2700 Oak Industrial Dr. NE, Grand Rapids, MI USA 49505-6026 616.459.3311 | www.ky.com

3. Product Description

Basic Use: 660 Series Heavy-Duty Round Tubing is manufactured for closet or other storage applications requiring closet rod support.

 $\textbf{Composition and Materials:} \ \textbf{Steel core with finished wrap}$

Sizes:

Outside Diameter: 1-1/16" Inside Diameter: 29/32" Wall Thickness: 0.087"

Lengths: 48", 60", 72", 96", 120", 144"
Finishes: Stainless Steel (SS) or Brass-look (BR).

4. Technical Data

Applicable Standards: Closet Rods are tested to meet or exceed ANSI performance standards as established by BHMA in the Knape & Vogt (KV) recommended application. These load limits are intended to be used as general guidelines only, and no warranty — expressed or implied — is made by Knape & Vogt.

Results were obtained by laboratory testing in accordance with ANSI/ BHMA A156.9-2003 performance standard.

Representative testing in a fully configured application is the only way to assure proper performance, durability, and safety.

The aforementioned load limit is intended as a guide only and not as a warranty. Actual load bearing capabilities depend upon the type of cabinet/wall material and use of appropriate mounting fasteners, installation technique, and construction.

Environmental Considerations:

Environment: Excessive humidity, salts, or other chemical agents can corrode the finish and attack metal or plastic components.

Fastening: Inadequate or incorrect fasteners can result in the flanges and rods pulling loose and causing damage.

Alignment: Improper closet rod alignment can result in a system that is ineffective and unsafe.

5. Installation

For maximum loading capacity, flanges and closet rod should be mounted into studs or a solid frame. Mark installation locations of flanges and secure them to studs or solid frame. Install closet rod into flanges. Always install additional supports in center of application if closet rod is 5 feet, or 32" instvals into wall studs if longer than 5 feet.

6. Availability and Cost

Availability: Knape & Vogt (KV) products are available from stocking distributors and through KV Representatives worldwide.

Cost: Current pricing is available from area KV Representatives. Please call for the nearest representative at: 1.800.253.1561.

7. Warranty

Limited Lifetime Warranty: Knape & Vogt offers its standard Limited Lifetime Warranty to the initial purchaser of commercial products. This warranty covers defects in materials and workmanship which occur during normal use, and the remedy is limited to repair or replacement of defective products, at KV's option. Certain types of defects and damage are excluded from warranty coverage, costs and expenses are not covered, and additional restrictions apply. A copy of the Limited Lifetime Warranty, with all warranty details, limitations and disclaimers, is available on the Customer Care Connection location at www.kv.com or from KV Customer Service, 2700 Oak Industrial Drive, Grand Rapids, MI 49505, 1.800.253.1561.

8. Maintenance

660 Series Heavy-Duty Round Closet Rods require no maintenance. Inspect for proper fit periodically and adjust when necessary. Replace as required or recommended by application.

9. Technical Services

Knape & Vogt and area representatives can assist with any application. For further information, or for the name of the representative nearest you, please call Knape & Vogt Customer Service: 1.800.253.1561 or visit our website at: www.kv.com.

10. Filing Systems

Additional product information, data sheets, application sheets, and a full catalog are available upon request from Knape & Vogt.



BHMA Knape & Vogt shelving products follow the ANSI testing standards established by BHMA.